

Compuprint 6214



The Compuprint 6214 is the entry level model of the new thermal product line. The Compuprint 6214 offers users a durable, technologically advanced thermal printer with the design principles that have proven successful in previous thermal printers. The small footprint makes the printer ideally suited for use when space is limited. The Compuprint 6214 is designed to address the desktop and light industrial marketplace with the performance and value required in these healthcare, light industrial, retail and shipping applications.

Powerful Barcode Printer for most demanding jobs

Full functions, powerful features, user friendly interface

and high extensibility make the **Compuprint 6214**

perfect for retail and industrial applications.



Color TFT LCD and operation panel for easy and intuitive operation



Ethernet, USB 2.0, Serial and USB host are standard features adding flexibility and power



Rod-less label roll holder for easy loading and smooth feeding



Innovative "C" button makes label Calibration simple and fast

TECHNICAL DATA		PRT6214	PRT6214-H
	Print Method	Thermal Transfer/Direct Thermal	
	Resolution	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)
	Print Speed	Up to 7 IPS (177 mm/s)	5 IPS (127 mm/s)
	Print Width	4.25" (108 mm)	4,16" (105,7 mm)
	Print Length	Min. 0.16" (4 mm)**; Max. 68" (1727 mm)	Min. 0,16" (4 mm) Max. 30"(762 mm)
Memory	Flash	8 MB Flash (4 MB for user storage)	
	SDRAM	16 MB SDRAM	
	Sensor Type	Adjustable reflective sensor (full range) Fixed transmissive sensor, central aligned	
Media	Types	Continuous form, gap labels, black mark sensing and punched hole; label length set by auto sensing or programming	
	Width	1" (25.4 mm) Min. - 4.64" (118 mm) Max.	
	Thickness	0.003" (0.06 mm) Min. - 0.01" (0.2 mm) Max.	
	Label Roll Diameter	Max. 5" (127 mm)	
	Core Diameter	1" (25.4 mm), 1.5" (38.1 mm)	
Ribbon	Types	Wax, wax/resin, resin	
	Length	981' (300 m)	
	Width	1.18" (30 mm) Min. - 4.33" (110 mm) Max.	
	Ribbon Roll Diameter	2.67" (68 mm)	
	Core Diameter	1" (25.4 mm)	
	Printer Language	CEL, CZL auto switch - CEL (Compuprint Eltron Language) CZL (Compuprint Zebra Language)	
Software	Label Design Software	CPLabel	
	Driver	Windows XP SP2 or later, Vista, Win7, Win8, Win8.1, Server 2003, 2008, 2008R2, 2012, 2012R2, 32 and 64 bit(x64)	
	DLL	Windows XP, Vista, Win7, Win8	
Resident Fonts	Bitmap Fonts	6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A&B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions	
	Scalable Fonts	90°, 180°, 270° rotatable	
	Bitmap Fonts	Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable	
Download Fonts	Asian Fonts	Asian fonts 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions	
	Scalable Fonts	Scalable fonts 90°, 180°, 270° rotatable	
	1-D Bar codes	Code 39, Code 93, EAN 8 /13 (add on 2 & 5), UPC A/E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar	
Barcodes	2-D Bar codes	PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code, Aztec code	
	Code Pages	CODEPAGE 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 WINDOWS 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode (UTF8, UTF16)	
	Graphics	Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software	
Interfaces		USB 2.0	
		Serial port: RS-232 (DB-9)	
		Ethernet 10/100 Mbps print server	
		USB Host	
Control Panel		Color TFT LCD with navigation button	
		Power on/off button	
		Calibration button	
	Real Time Clock	Standard	
	Power	Auto Switching 100-240VAC, 50-60Hz	
Environment	Operation Temperature	41°F to 104°F (5°C to 40°C)	
	Storage Temperature	-4°F to 122°F (-20°C to 50°C)	
Humidity	Operation	30-85%, non-condensing	
	Storage	10-90%, non-condensing	
	Agency Approvals	CE(EMC), FCC Class A, CB, CCC, cUL	
Dimension	Length	11.0" (280 mm)	
	Height	7.3" (186 mm)	
	Width	8.3" (210 mm)	
	Weight	6.6 lbs (3 Kg), excluding consumables	
	Options	Guillotine Cutter Label Dispenser External Label Unwind Stand 2" - 4"	



Compuprint S.r.l.

Via Cottolengo 75-77-79
10072 Caselle T.se (TO)

Sales Contact

Tel. +39 011 9892 141 - Fax +39 011 9974432

sales@compuprint.com

www.compuprint.com